# 3610 RESIDENTIAL STEEL



**3650** Insulated Flush Panel

doorLink
Manufacturing, Inc.®

## **Features:**

- Sandwich type construction with CFC free expanded polystyrene insulation pressure bonded between two sheets of 26 gauge hot dipped galvanized steel with a 10.25 R value.
- 1.0 mil paint system includes .25 mil rust inhibiting primer and .75 mil exterior top coat that resists fading and chalking while providing consistent color from panel to panel.
- 20 gauge hot dipped galvanized steel hinge plates run the full height of each section at all hinge locations to facilitate the attachment of hinges, handles, struts and step plates.
- · Rigid aluminum retainer provides added strength while securing replaceable U-shaped bottom weatherstrip.
- Sections include tongue and groove meeting rails for superior strength and better sealing against wind, rain and snow.

# **Cut-away view:**

- groove meeting rails. · CFC free expanded polystyrene insulation.
- retainer

Sandstone



# **Colors Available:**



Desert Tan





Sizes Available:		HEIGHTS AVAILABLE:
DOOR WIDTH	PANELS WIDE	6'6", 6'9", 7'0", 7'6", 7'9", 8'0"
8', 9' 10' 12' 14', 15' 16', 17', 18' 20'		

Not all glazing options may be available from all distributors.

## **Authorized Dealer:**



